



Adapt™ Premium Commercial Tankless

Ultra Force® Technology without the Tank

Adapt Tankless Powered by Ultra Force is the tankless water heater that utilizes the same helical heat exchanger technology that's made State water heaters reliable for decades—just without the tank. Which means you've got all the thermal efficiency and installation flexibility you need in a more compact unit that adapts to your needs.



Powered by Ultra Force:

- Single stainless steel, heavy-duty heat exchanger design eliminates most internal welds and improves overall reliability
- More resilient to corrosion, scale buildup and resultant leaks

High Efficiency:

- 199,000 BTU/h
- 9,000 BTU min. input
- 22:1 Turndown Ratio
- Max Flow Rate 10.5 GPM; 0.4 GPM activation; 0.26 GPM for continuous fire
- 0.95 UEF, ENERGY STAR® certified

96% Thermal Efficiency

Flexible Installs:

- Universal indoor or outdoor installation; Outdoor Vent Cap Kit sold separately
- ½" Gas Line or larger
- Exhaust venting, 2" PVC up to 75' (23 m); 3" PVC up to 150' (45.7 m)
- Common vent up to 12 units
- Outdoor rated power cord standard on every unit
- Cascade up to 32 units with single cable per heater, cable included
- Wi-Fi and Building Maintenance System (BMS) connectivity (accessory modules sold separately)
- Optional X3 Scale Prevention Technology (cartridge sold separately)

Model Number*	Gas Consumption Input		UEF	Dimensions			Approx Shipping Weight (lbs)	Warranty Term
	Minimum BTU	Maximum BTU		Height	Width	Depth		
SCTH-199M-N	9,000	199,000	0.95	33.8"	16.5"	16.1"	117 lb.	8 / 5 / 1

8-year limited warranty on heat exchanger; 5-year limited warranty on all parts; and, 1-year limited warranty on labor in commercial applications.

